

Product Information Sheet

Coastline



Made in Canada



RoHS compliant



REACH compliant



ISO9001: 2015 certified by Intertek



IMO MED certified



Formulated without Ortho-Phthalates



100% Vegan Leather

Physical Properties



PVC + Polyester



745g (± 70)



137cm (+5)



1,0mm (± 0,1)



300 000 cycles



Newton/25.4mm
W: ≥13
F: ≥13

Property	Method	Standard	Tolerance
Crocking	CFFA 7; AATCC-TM 8	Rating Wet: Good; AATCC 4-5 min. Rating Dry: Good; AATCC 4-5 min.	
Tensile* (N)	ASTM D751	MD: 423	CMD: 338
Single Tear* (N)	CFFA 16; ASTM D2261	MD: 40	CMD: 40
Trapezoid Tear* (N)	ASTM D751	MD: 113	CMD: 129
Stretch Under Load* (%)	SAE J855	MD: 48	CMD: 130
Permanent Set* (%)	SAE J855	MD: 7	CMD: 21

*Typical Values: These values are average results, not minimums.

*MD: Machine Direction. CMD: Cross-Machine Direction

Market Application Features

Property	Method	Standard
Weather Resistance / UV Resistance	ASTM G153; Cycle 1, 1 000 hrs	No significant colour change or stiffening, Min AATCC 4, UV coefficient ≥7 Blue Wool scale
Mildew Resistance	ASTM G21	No growth or discolouration
Blocking Resistance	CFFA 4	2 max.
Cold Resistance (°C)	CFFA 6a (vinyl out)	-32; no cracking of the skin
Stain Resistance	MI-QAWI-203	Colour variation not exceeding AATCC 4 after cleaning
IMO MED Wheelmark	COA 164144-15 20190508	



Fire Retardancy

EN 1021 Part 1 & 2
(MED) Marine Equipment Directive
IMO FTP 2010 Code MSC 88/26/ADD.2 Part 8 3.1 & 3.2
FMVSS 302
CAL TB 117-2013, Section E

Note: The information stated is, to the best of our knowledge, accurate. It is offered for verification and reference purposes only. offers no warranty and assumes no liability for actual reliance on this information.

Note: This product Information Sheet contains both quality and design specifications.

Supplied by Vyva Fabrics

Revised: June 22, 2020 Rev.8